

Enclosures

MATERIAL	DMC (Dough Moulding Compound)
OPERATING TEMPERATURE	-50° C to + 200° C
GLOW WIRE CAPABILITY / FLAMMABILITY	960° / UL94 V0
EXPECTED UV LIFE (DIRECT EXPOSURE)	25 years +
IP LEVEL	IP54
SECURITY LEVEL	With RL the security level differs between products. Please note individual security rating.
ENVIRONMENT (INDOOR/OUTDOOR)	Indoor and Outdoor use

Hinges

RL and AP series enclosures preceded the more modern and functional range of enclosures we call Allbrox. Although superseded for the most part, there are still some applications where these tried and tested versions are preferred.

Locks



Security Level: 2

Part Number	Description	H	W	D	Description	QTY
040-727	RL-1P	150	150	100	Plain (Screw fastened Lid)	20
040-726	RL-1HW/L	150	150	100	Hinged with window	20
040-725	RL-1HP	150	150	100	Hinged plain box	20

Handles



Security Level: 2

Part Number	Description	H	W	D	Description	QTY
040-730	RL-2P	200	145	100	Plain (Screw Fastened Lid)	4
040-728	RL-2HP	200	145	100	Hinged plain box	4
040-729	RL-2HW	200	145	100	Hinged with window	4
040-766	RL-2CP	200	145	165	Plain (Screw Fastened Lid)	4
040-764	RL-2CHP	200	145	165	Hinged plain box	4
040-765	RL-2CHW	200	145	165	Hinged with window	4

Note: C = Deep Base, Shallow Lid

Rotary Operating Handles



Security Level: 2

Part Number	Description	H	W	D	Description	QTY
040-769	RL-3P	260	220	230	Plain (Screw fastened Lid)	3
040-767	RL-3HP	260	220	230	Hinged plain box	3
040-768	RL-3HW	260	220	230	Hinged with window	3

Insulators

Transformer Equipment



Security Level: 2

Part Number	Description	H	W	D	Description	QTY
040-733	RL-4P	350	250	160	Plain (Screw fastened Lid)	2
040-731/L	RL-HP	350	250	160	Hinged plain with latch	2
040-732/L	RL-4HW	350	250	160	Hinged window with latch	2
040-734	RL-4DHP	350	250	200	Hinged Deep plain box	4
040-735	RL-4DHW	350	250	200	Hinged with window Deep	4

Note: Special wired pole mounted enclosures available on request.

Index



Security Level: 3

Part Number	Description	H	W	D	Description	QTY
040-738	RL-5P	390	300	200	Plain (Screw fastened Lid)	3
040-736/L	RL-5HP	390	300	200	Hinged plain with latch	3
040-737/L	RL-5HW	390	300	200	Hinged window with latch	3
040-741	RL-5BP	390	300	141	Plain (Screw fastened Lid)	3
040-739	RL-5BHP	390	300	141	Hinged plain box	3
040-740	RL-5BHW	390	300	141	Hinged with window	3

Note: B = Shallow Lid
 Orange colour available on request - used here for illustration only.
 Standard colour is GREY.



Security Level: 3

Part Number	Description	H	W	D	Description	QTY
040-640	RL-6D-P	480	315	200	Hinged plain box deep	1



Security Level: 3

Part Number	Description	H	W	D	QTY
AP2-A	AP2-A (DB-1 Shallow)	600	450	165	1



Security Level: 3

Part Number	Description	H	W	D	QTY
AP3-A	AP3-A (DB-1 Deep)	600	450	260	1
AP3-S	AP3-S (DB-1T Box - Thin)	600	450	75	1



Part Number	Description	H	W	D
020-293	PB-small B-A	27	124	22
020-292	PB-medium B-B	31	147	30
020-291	PB-large B-C	27	250	55
020-081	DMC DEVICE PLATE RL2 (DEV-D)	195	40	3
020-082	DMC DEVICE PLATE RL1 (DEV-C)	145	145	3
020-083	DMC DEVICE PLATE RL3A (DEV-G)	255	215	3
020-084	DMC DEVICE PLATE RL3 (DEV-H)	255	215	3
020-085	DMC DEVICE PLATE RL4 (DEV-O)	345	240	3
020-086	DMC DEVICE PLATE RL5 (DEV-Q)	385	295	3

Enclosures
Hinges
Locks
Handles
Accessories
Rotary Operating Handles
Insulators
Transformer Equipment
Index